



IT210

Level Converter, Direction Signal Decoder and programmable pulse divider

Product features:

- Level Converter (RS-422, HTL Single Ended, HTL Differential, TTL and and vice-versa)
- Implementation between the two types of representations for the direction of rotation (A/B 90 °, A/B Direction and vice versa)
- Adjustable division ratio of directional A / B pulses
- Adjustable division ratio for the Z pulse
- Reset of the Z divider by external input (defined setting)
- Zero setting of the A / B / Z divider by external input (defined Start / Stop)
- Z divider can also be used as an independent second divider
- Limit frequency up to 1 MHz, depending on the input format
- Push-pull outputs direct SPS control
- 9 to 30 VDC power supply

Technical Specifications		
Connections:	Connector type:	screw terminal, 1.5 mm ² / AWG 16
Power supply:	Input voltage: Protection circuit: Ripple: Consumption:	9 ... 30 VDC reverse polarity protection ≤ 10 % approx. 40 mA (at 9 V, unloaded) approx. 30 mA (at 30 V, unloaded)
Sensor supply:	Output voltage: Output current:	+ 5,5 VDC +/- 5 % max. 250 mA
Incremental inputs:	Number of inputs: Channels: Configuration: RS422: HTL Differential: HTL Single Ended: TTL:	3 A, B, Z (HTL Single Ended, TTL) A, /A, B, /B, Z, /Z (RS422, HTL Differential) RS422, HTL Differential, HTL Single Ended, TTL max. 1 MHz (RS422 difference signal > 1 V) max. 1 MHz (HTL difference signal > 2 V) max. 350kHz, Level 1: Low 0 ... 10V, High 14 ... 30 V Level 2: Low 0 ... 5V, High 9 ... 30 V max. 350kHz, Low 0 ... 0.7V, High 2.2 ... 5V
Control inputs:	Number of inputs: Format: Frequency: Reaction time: Load:	2 HTL, PNP (Low 0 ... 5 V, High 9 ... 30 V) max. 20 kHz 50 μs max. 3mA
Incremental outputs:	Number of inputs: Channels: Signal level: Output current: Reaction time	3 A, /A, B, /B, Z, /Z HTL: 8 ... 29 V (Depending on supply voltage) RS422: 5 V max. 20 mA / Push-Pull ca. 600ns
Housing:	Material: Mounting: Dimensions (w x h x d): Protection class: Weight:	plastic 35mm top hat rail (according to EN60715) 22,5x 102 x 102 mm / 0,886 x 4,016 x 4,016" IP20 approx. 100 g
Ambient temperature:	Operation: Storage:	0 °C ... +60 °C / +32 ... +140 °F (not condensing) -25 °C ... +70 °C / -13 ... +158 °F (not condensing)
Failure rate:	MTBF in years:	109,3 (long-term usage at 60 °C / 140 °F)
Conformity & standards:	EMC 2014/30/EU: RoHS (II) 2011/65/EU RoHS (III) 2015/863:	EN 61000-6-2, EN 61000-6-3, EN 61000-6-4, EN 61326-1 EN IEC 63000